



**Flammable, toxic and
Oxygen gas detector for
industrial applications**

Sensepoint XCD



One-Stop Shop

- Flammable (catalytic or infrared), toxic and Oxygen versions available
- New and retrofit applications
- Suitable for indoor or outdoor use
- Stainless steel or aluminium explosion-proof housing options
- IP66 as standard

Proven and Reliable Sensor Technology

- Surecell™ electrochemical sensors
- Poison immune infrared sensors
- Poison resistant catalytic bead sensors
- Long life sensors

Global Approvals

- European, North American and Asian
- Compliant with ATEX, IECEx, UL/c-UL, KTL, PA, GB and CCCF standards

Easy to Use

- User friendly and intuitive tri-colour backlit display with digits, bar graph and icons
- Fully configurable via magnetic switches
- Selectable sink or source 4-20mA output
- Auto-inhibit during maintenance
- Optional MODBUS communications for remote diagnostics/configuration

Cost Effective

- Common transmitter platform
- Minimal training required
- Reduced spares
- Non-intrusive, one-man operation
- Plug-in sensor replacement
- Optional MODBUS multi drop option offers cabling savings

Simple Installation

- Plug-in display module removes to give access to terminal area
- Integral mounting bracket
- 2 x M20 or ¾" NPT cable/conduit entries (certification dependent)
- Removable plug/socket type terminal blocks for ease of wiring
- Sink/source switch to suit preferred wiring topology

Range of Optional Accessories

- Sunshade/deluge protection
- Duct mounting kit
- Calibration gas flow housing
- Collecting cone

The Sensepoint XCD range provides comprehensive monitoring of flammable, toxic and Oxygen gas hazards in potentially explosive atmospheres, both indoors and outdoors. Users can modify detector operation using the LCD and magnet switches without ever needing to open the unit. This enables one-man, non-intrusive operation and reduces routine maintenance time and costs.

A tri-colour backlit LCD clearly indicates the unit's status at a glance, even from a distance. A steady green backlight indicates normal operation, flashing yellow indicates fault and flashing red indicates an alarm.

All detectors are supplied pre-configured and include 2 programmable alarm relays, 1 programmable fault relay as well as an industry standard 4-20mA output (sink or source selectable) and MODBUS.

The scale, range, relay operation, alarm set point and electronic tag number of the detector can be adjusted using the transmitter's LCD and non-intrusive magnetic switches. Outputs are automatically inhibited during adjustment, thereby reducing the risk of false alarm at the control panel during maintenance.

Sensepoint XCD has an integral mounting plate for surface mounting or can be mounted to a horizontal or vertical pipe using the optional pipe mounting bracket. Electrical installation can be made using either conduit or cable with suitable mechanical protection. Two M20 or ¾"NPT entries are provided (depending on certification). A weatherproof cap is also included for use in the harshest outdoor conditions. Other optional accessories include a sunshade/deluge protection, duct mounting kit and collecting cone.

Sensepoint XCD ensures easy installation and the fastest routine operation by removing the need for hot work permits in hazardous areas. Using easy to replace plug-in sensors, downtime is also reduced and on-going costs are minimised through the use of poison resistant flammable sensors, poison immune infrared Hydrocarbon sensors and patented Surecell™ toxic sensors.



Typical Applications

- Industrial manufacturing facilities
- Power plants
- Waste water facilities
- Utilities
- Food and beverage production
- Refineries and chemical plants
- Onshore oil and gas terminals
- Production platforms
- Exploration and drilling

Sensepoint XCD Overview



There are three different types of the XCD transmitter for use with three different families of sensors.


The mV type transmitter is for use with the mV family of XCD sensors including catalytic sensors to detect flammable gases in the range 0-100%LEL and infrared (IR) sensors for detection of Hydrocarbon gases in the range 0-100%LEL. Two IR Hydrocarbon sensors are available; one linearised to Methane and one linearised to Propane. The Propane version has linear cross sensitivities factors for Ethylene, Butane and Pentane. There is also an IR CO₂ sensor available in the range 0-2%Vol.

The EC type transmitter is for use with the EC family of XCD sensors including Carbon Monoxide (CO), Hydrogen Sulphide (H₂S), Nitrogen Dioxide (NO₂) and Hydrogen (H₂).

The Oxygen transmitter is for use with the Oxygen (O₂) XCD sensors.

A transmitter can auto-recognise any sensor from within its sensor family. The sensor simply plugs into the bottom of the transmitter and the transmitter automatically configures itself accordingly.

| Sensepoint XCD Sensor Families, Gases and Ranges | | | | | | | | |
|--|------------------|----------------------------------|------------------|-----------|--|-------------------|-----------|-----------|
| | Gas | User Selectable Full Scale Range | Default Range | Steps | Selectable Cal Gas Range | Default Cal Point | | |
| Sensor Family | mV | Catalytic Bead Sensors | | | 30 to 70% of selected full scale range | | | |
| | | Flammable 1 to 8* | 20 to 100%LEL | 100%LEL | | | 10%LEL | 50%LEL |
| | | Infrared Sensors | | | | | | |
| | | Methane | 20 to 100%LEL | 100%LEL | | | 10%LEL | 50%LEL |
| | | Propane | 20 to 100%LEL | 100%LEL | | | 10%LEL | 50%LEL |
| | | Carbon Dioxide | 2.00%Vol. only | 2.00%Vol. | | | n/a | 1.00%Vol. |
| | | Electrochemical Sensors | | | | | | |
| | | Hydrogen Sulphide | 10.0 to 100.0ppm | 50.0ppm | | | 0.1ppm | 25ppm |
| | | Carbon Monoxide | 100 to 1,000ppm | 300ppm | | | 100ppm | 100ppm |
| | | Hydrogen | 1,000ppm only | 1,000ppm | | | n/a | 500ppm |
| | Nitrogen Dioxide | 10.0 to 50.0ppm | 10.0ppm | 5.0ppm | 5.0ppm | | | |
| | O ₂ | Oxygen | 25.0%Vol. only | 25.0%Vol. | n/a | 20.9%Vol. (Fixed) | 20.9%Vol. | |



Ready, Steady, Go!

Sensepoint XCD uses three instantly recognisable 'traffic light' colours to indicate its status. The large tri-colour backlit LCD is steady green to indicate normal operation, flashes yellow to indicate a fault/warning and flashes red to indicate an alarm. This allows anyone in the area to clearly see at a glance the status of any detector. This can be particularly useful to identify detector status if the detector is located in a difficult to access area or if a number of detectors are located in the same area.




Installation



Outline Installation Dimensions


The Sensepoint XCD transmitter has an integral mounting plate consisting of four mounting holes on the transmitter body. The transmitter may be fixed directly to a surface mounting, or to a horizontal or vertical pipe/structure, 40.0-80.0mm (1.6 to 3.1") in diameter/cross section. The pipe mounting bracket accessory (optional) may be used for this purpose.

User cable entries shown (2 x M20) are for ATEX/IECEx version enclosures. UL/c-UL versions have 2 x 3/4"NPT conduit entries. A suitable blanking plug is supplied which must be used to seal any unused entry. The blanking plug must be suitably sealed to maintain the IP rating of the detector.




All dimensions in mm.
1" = 25.4mm


Installation Options



Wall Mounted




Vertical or horizontal pipe mounted
(Using optional pipe mounting bracket)





Duct Mounted

Other Accessories


Various accessories are available for different applications:



Sunshade/Deluge protection



Collecting Cone



Gassing Cap

Installation




Electrical

Sensepoint XCD is designed for use in potentially explosive atmospheres. As such, installation should follow national guidelines using suitable mechanically protected cable and glands or conduit. Use 0.5mm² (20AWG) to 2.5mm² (~13AWG) cross sectional area cable as needed to ensure minimum operating voltage at the detector, depending on installed cable length. Cable diameter should be selected to maintain the minimum required voltage for the longest installed cable length under maximum power.


Terminal Module Connections

| Terminal Number | Marking | Connection | Description |
|-----------------|----------|-------------------------|---|
| 1 | 24V | +VE Supply (16 - 32VDC) | Controller Connections |
| 2 | 0V | -VE Supply (OVDC) | |
| 3 | 4~20mA | Current Output Signal | |
| 4 | COM | Drain | MODBUS RTU. RS485 (Optional) |
| 5 | TxD | MODBUS B (+) | |
| 6 | RxD | MODBUS A (-) | |
| 7 | RLY1/NC | Normally Closed | Programmable Relay 1 (Default A1) |
| 8 | RLY1/COM | Common | |
| 9 | RLY1/NO | Normally Open | |
| 10 | RLY2/NC | Normally Closed | Programmable Relay 2 (Default A2) |
| 11 | RLY2/COM | Common | |
| 12 | RLY2/NO | Normally Open | |
| 13 | RLY3/NC | Normally Closed | Programmable Relay 3 (Default Fault) |
| 14 | RLY3/COM | Common | |
| 15 | RLY3/NO | Normally Open | |

Internal Earth/
Ground Point



Terminal Module



Puck Rear View

Note: Terminal Blocks are plug/socket type and may be removed to ease wiring.


Typical Cable Lengths

| Typical Cable Data | | | Maximum Cable Length | | | | | |
|--------------------------------------|------------------|------|----------------------|------|--------|------|--------|------|
| Cable Size (Cross Sectional Area) | Cable Resistance | | Catalytic | | EC | | IR | |
| | Ω/km | Ω/mi | Metres | Feet | Metres | Feet | Metres | Feet |
| 0.5mm ² (20AWG*) | 36.8 | 59.2 | 356 | 1167 | 478 | 1568 | 420 | 1379 |
| 1.0mm ² (17AWG*) | 19.5 | 31.4 | 671 | 2201 | 902 | 2956 | 793 | 2599 |
| 1.5mm ² (16AWG*) | 12.7 | 20.4 | 1031 | 3387 | 1384 | 4549 | 1217 | 4000 |
| 2.0mm ² (14AWG*) | 10.1 | 16.3 | 1296 | 4239 | 1741 | 5694 | 1531 | 5006 |
| 2.5mm ² (13AWG*) | 8 | 12.9 | 1636 | 5356 | 2197 | 7194 | 1932 | 6326 |


Note: Table given for guidance only. Users should calculate maximum distances using actual data for cable being used. Typical calculation assumes minimum guaranteed controller supply of 24VDC, minimum detector voltage of 16VDC and maximum power supply under full alarm. R_L (max) is 250ohms.

Wiring Schematics

The Sensepoint XCD transmitter may be wired in either Current Sink or Current Source configuration. These two options are offered to allow greater flexibility in the type of control system that it can be used with. Sink/Source is selectable via the switch located on the back side of the display module; accessible by removing the display module during installation/ commissioning.



XCD Source Configuration



XCD Sink Configuration

Note: Terminate cable screen at the detector or the controller, not both.



Technical Summary




| Sensepoint XCD Detector | | | | | | | | | | | |
|--|--|---|--------|--|-------------------|--------------------------|---------------|------------------------|--------------|----------------------|-------------|
| Use | 3 wire, 4-20mA and RS485 MODBUS output fixed point detector with in-built alarm and fault relays for the protection of personnel and plant from flammable, toxic and Oxygen hazards. Incorporating a transmitter with local display and fully configurable via non-intrusive magnetic switch interface. Wide range of sensors available. | | | | | | | | | | |
| Electrical | | | | | | | | | | | |
| | Input Voltage Range | 16 to 32VDC (24VDC nominal) | | | | | | | | | |
| | Max Power Consumption | Maximum power consumption is dependent on the type of gas sensor being used. Electrochemical cells = 3.7W, IR = 3.7W and catalytic = 4.9W. Maximum inrush current = 800mA at 24VDC | | | | | | | | | |
| | Current Output | Sink or source | | | | | | | | | |
| | ≥0.0<1.0mA | Fault | | | | | | | | | |
| | 2.0mA or 4.0mA (17.4mA) | Inhibit (during configuration/user settings) | | | | | | | | | |
| | 4.0mA to 20.0mA | Normal gas measurement | | | | | | | | | |
| | 22.0mA | Maximum over range | | | | | | | | | |
| | Terminals | 15 x screw terminals suitable for wire diameter 0.5mm ² to 2.5mm ² (20AWG to 14AWG) | | | | | | | | | |
| | Relays | 3 x 5A@250VAC. Selectable normally open or normally closed (switch) and energised/de-energised (programmable) Alarm relays default normally open/de-energised. Fault relay default normally open/energised | | | | | | | | | |
| | Communication | RS485, MODBUS RTU (Optional) | | | | | | | | | |
| Construction | | | | | | | | | | | |
| Material | Housing | Epoxy painted aluminium alloy LM25 or 316 stainless steel | | | | | | | | | |
| | Sensor | 316 stainless steel | | | | | | | | | |
| | Weather Protection | Plastic | | | | | | | | | |
| Weight (approx) | Aluminium Alloy LM25 | 2.0kg (4.4lbs) | | | | | | | | | |
| | 316 Stainless Steel | 5.0kg (11lbs) | | | | | | | | | |
| Mounting | Integral mounting plate with 4 x mounting holes suitable for M8 bolts Optional pipe mounting kit for horizontal or vertical pipe Ø1.5 to 3" (2" nominal) | | | | | | | | | | |
| Entries | European ATEX/IECEx versions: 2 x M20 cable entries North American UL/c-UL versions: 2 x ¾"NPT conduit entries. Suitable blanking plug supplied for use if only 1 entry used. Seal to maintain IP rating | | | | | | | | | | |
| Detectable Gases and XCD Sensor Performance | | | | | | | | | | | |
| Gas | User Selectable Full Scale Range | Default Range | Steps | User Selectable Cal Gas Range | Default Cal Point | Response Time (T90) Secs | Accuracy | Operating Temperature* | | Default Alarm Points | |
| | | | | | | | | Min | Max | A1 | A2 |
| Electrochemical Sensors | | | | | | | | | | | |
| Oxygen | 25.0%Vol. only | 25.0%Vol. | n/a | 20.9%Vol. (Fixed) | 20.9%Vol. | <30 | <+/-0.5%Vol. | -20°C / -4°F | 55°C / 131°F | 19.5%Vol. ▼ | 23.5%Vol. ▲ |
| Hydrogen Sulphide | 10.0 to 100.0ppm | 50.0ppm | 1ppm | 30 to 70% of selected full scale range | 25ppm | <50 | <+/-1ppm | -20°C / -4°F | 55°C / 131°F | 10ppm ▲ | 20ppm ▲ |
| Carbon Monoxide | 100 to 1,000ppm | 300ppm | 100ppm | | 100ppm | <30 | <+/-6ppm | -20°C / -4°F | 55°C / 131°F | 100ppm ▲ | 200ppm ▲ |
| Hydrogen | 1,000ppm only | 1,000ppm | n/a | | 500ppm | <65 | <+/-25ppm | -20°C / -4°F | 55°C / 131°F | 200ppm ▲ | 400ppm ▲ |
| Nitrogen Dioxide | 10.0 to 50.0ppm | 10.0ppm | 5.0ppm | | 5.0ppm | <40 | <+/-3ppm | -20°C / -4°F | 55°C / 131°F | 5.0ppm ▲ | 10.0ppm ▲ |
| Catalytic Bead Sensors | | | | 25 to 95% of selected full scale range | | | | | | | |
| Flammable 1 to 8* | 20 to 100%LEL | 100%LEL | 10%LEL | | 50%LEL | <25 | <+/-1.5%LEL | -20°C / -4°F | 55°C / 131°F | 20%LEL ▲ | 40%LEL ▲ |
| Infrared Sensors | | | | 30 to 70% of selected full scale range | | | | | | | |
| Methane | 20 to 100%LEL | 100%LEL | 10%LEL | | 50%LEL | <30 | <+/-1.5%LEL | -20°C / -4°F | 50°C / 122°F | 20%LEL ▲ | 40%LEL ▲ |
| Propane | 20 to 100%LEL | 100%LEL | 10%LEL | | 50%LEL | <30 | <+/-1.5%LEL | -20°C / -4°F | 50°C / 122°F | 20%LEL ▲ | 40%LEL ▲ |
| Carbon Dioxide | 2.00%Vol. | 2.00%Vol. | n/a | | 1.00%Vol. | <30 | <+/-0.04%Vol. | -20°C / -4°F | 50°C / 122°F | 0.40%Vol. ▲ | 0.80%Vol. ▲ |
| <p>NOTES</p> <p>Performance data is: 1. Taken at nominal 20°C, 50%RH. 2. Applicable over the range 10 to 90% full scale. 3. Measured on units calibrated at 50% full scale. 4. Accuracy at 10% of default full scale (typical A1 alarm) of applied gas, or minimum (whichever is greater). 5. Measured at 500ml/min for IR, Toxics and O₂, 1 Ltr/min for Catalytic bead using the calibration cup (S3KCAL).</p> <p>*Extended operating temperature range of -40°C to +65°C (-40°F to +149°F) for all sensors except for IR and H₂ EC sensors, with an accuracy of +/- 30% of applied gas from -20°C to -40°C (-4°F to -40°F) and +55°C to +65°C (+131°F to +149°F). Long term operation at this range may cause decline in sensor performance. Contact Honeywell Analytics for any additional data or details.</p> | | | | | | | | | | | |
| Certification | | | | | | | | | | | |
| European | ATEX Ex II 2 GD Ex d IIC Gb T6 (Ta -40°C to +65°C) Ex tb IIIC T85°C Db IP66 | | | | | | | | | | |
| International | IEC Ex d IIC Gb T6 (Ta -40°C to +65°C) Ex tb IIIC T85°C Db IP66 | | | | | | | | | | |
| China | GB Ex d IIC T4 GB3836.1&2 -2000, PA, CCCF | | | | | | | | | | |
| Korea | KTL Ex d IIC T6 (-40°C to +65°C) | | | | | | | | | | |
| North America | UL/c-UL - Class I, Division 1, Groups B, C and D, Class I, Division 2, Groups B, C & D, Class II, Division 1, Groups E, F & G, Class II, Division 2, Groups F & G. -40°C to +65°C | | | | | | | | | | |
| EMC | CE: EN50270:2006 EN6100-6-4:2007 | | | | | | | | | | |
| Performance | ATEX, IEC/EN60079-29-1:2007, EN45544, EN50104, EN50271 China: PA Pattern Measurement (for transmitter and toxic gas sensors) "CCCF" Shenyang for Flammable (fire dept approval) CSA C22.2-152 | | | | | | | | | | |

▲ - Rising Alarm ▼ - Falling Alarm

Technical Summary cont. and Ordering Information



| | |
|------------------------------------|--|
| Environmental | |
| IP Rating | IP66 in accordance with EN60529:1992 |
| Certified Temperature Range | -40°C to +65°C (-40°F to +149°F) Note: The detector display may become illegible at temperatures below -20°C, but the detector continues its gas monitoring function. The display is not damaged and recovers when the temperature rises back above -20°C. |
| Operating Humidity | Continuous 20-90%RH (non-condensing), Intermittent 0-99%RH (non-condensing) |
| Operating Pressure | 90-110kPa |
| Storage Conditions | -25°C to +65°C (-13°F to 131°F) |
| Ordering Information | |
| Standard Supply | Sensepoint XCD is supplied complete with integral wall mounting plate, 2 x M20 cable entry (ATEX/IECEx) or 2 x ¾"NPT conduit entries (UL/CSA), 1 x M20 or 1 x ¾"NPT plug, Allen key for locking screw, weatherproof cap, operating magnet, sensor cartridge with retainer, quick start guide and instruction manual CD. Default settings, ranges and calibrations are 100% tested at the factory. Each unit is supplied with a calibration and test certificate. |
| Shipping Details | Shipping carton dimensions: L312mm (12.3") x W223mm (8.8") x D110mm (4.3") Approximate weight: Aluminium 2.5kg (5.5lbs), Stainless Steel 5.5kg (12.1lbs) |



Sensepoint XCD Detector ATEX/IECEx/KTL, PA & GB (Aluminium LM25)*

| | |
|-------------------|--|
| SPXCDALMFX | ATEX/IECEx/KTL/PA and GB approved SP XCD Flammable CAT 0-100%LEL (20 to 100%LEL, 10%LEL) with LM25, M20 Entry |
| SPXCDALMRX | ATEX/IECEx/KTL/PA and GB approved SP XCD (Methane) IR 0-100%LEL (20 to 100%LEL, 10%LEL) with LM25, M20 Entry |
| SPXCDALMPX | ATEX/IECEx/KTL/PA and GB approved SP XCD (Propane) IR 0-100%LEL (20 to 100%LEL, 10%LEL) with LM25, M20 Entry |
| SPXCDALMO1 | ATEX/IECEx/KTL/PA and GB approved SP XCD Oxygen 25.0%Vol. with LM25, M20 Entry |
| SPXCDALMHX | ATEX/IECEx/KTL/PA and GB approved SP XCD Hydrogen Sulphide 0-50.0ppm (10.0 to 100.0ppm, 1.0ppm) with LM25, M20 Entry |
| SPXCDALMCX | ATEX/IECEx/KTL/PA and GB approved SP XCD Carbon Monoxide 0-300ppm (100-1000ppm, 100ppm) with LM25, M20 Entry |
| SPXCDALMG1 | ATEX/IECEx/KTL/PA and GB approved SP XCD Hydrogen 0-1000ppm with LM25, M20 Entry |
| SPXCDALMNX | ATEX/IECEx/KTL/PA and GB approved SP XCD Nitrogen Dioxide 0-50.0ppm (10.0-50.0, 5.0ppm) with LM25, M20 Entry |
| SPXCDALMB1 | ATEX/IECEx/KTL/PA and GB approved SP XCD Carbon Dioxide IR 0-2.00%Vol. with LM25, M20 Entry |

Sensepoint XCD Detector ATEX/IECEx/KTL, PA & GB (316 Stainless Steel)*

| | |
|--------------------|--|
| SPXCDASLFX | ATEX/IECEx and AP approved SP XCD Flammable CAT 0-100%LEL (20 to 100%LEL, 10%LEL) with 316SS, M20 Entry |
| SPXCDASLRX | ATEX/IECEx and AP approved SP XCD (Methane) IR 0-100%LEL (20 to 100%LEL, 10%LEL) with 316SS, M20 Entry |
| SPXCDASLPX | ATEX/IECEx and AP approved SP XCD (Propane) IR 0-100%LEL (20 to 100%LEL, 10%LEL) with 316SS, M20 Entry |
| SPXCDASLMO1 | ATEX/IECEx and AP approved SP XCD Oxygen 25.0%Vol. with 316SS, M20 Entry |
| SPXCDASLMHX | ATEX/IECEx and AP approved SP XCD Hydrogen Sulphide 0-50.0ppm (10.0 to 100.0ppm, 1.0ppm) with 316SS, M20 Entry |
| SPXCDASLXCX | ATEX/IECEx and AP approved SP XCD Carbon Monoxide 0-300ppm (100-1000ppm, 100ppm) with 316SS, M20 Entry |
| SPXCDASLXG1 | ATEX/IECEx and AP approved SP XCD Hydrogen 0-1000ppm with 316SS, M20 Entry |
| SPXCDASLXNX | ATEX/IECEx and AP approved SP XCD Nitrogen Dioxide 0-50.0ppm (10.0-50.0, 5.0ppm) with 316SS, M20 Entry |
| SPXCDASLXB1 | ATEX/IECEx and AP approved SP XCD Carbon Dioxide IR 0-2.00%Vol. with 316SS, M20 Entry |

Optional Accessories

| | |
|---------------------|---|
| S3KCAL | Calibration cup |
| SPXCDCC | Collecting cone for use with lighter than air gases |
| SPXCDDMK | Duct mounting kit |
| SPXCDHMANEN | Hard copy manual in English |
| SPXCDMTBR | Mounting bracket (inc. bolts, nuts, brackets) |
| SPXCDSDP | Sunshade/Deluge Protection |
| 00780-A-0100 | ATEX approved junction box (Explosion-proof) |

Spare XCD Sensors (316 Stainless Steel)

| | |
|--------------------|--|
| SPXCDXSFSS | Flammable CAT 0-100%LEL (20 to 100%LEL, 10%LEL)** |
| SPXCDXSRSS | Methane IR 0-100%LEL (20 to 100%LEL, 10%LEL)** |
| SPXCDXSPSS | Propane IR 0-100%LEL (20 to 100%LEL, 10%LEL)** |
| SPXCDXS01SS | Oxygen 25.0%Vol. only |
| SPXCDXSHSS | Hydrogen Sulphide 0-50.0ppm (10.0 to 100.0ppm, 1.0ppm)** |
| SPXCDXSCSS | Carbon Monoxide 0-300ppm (100-1000ppm, 100ppm)** |
| SPXCDXSG1SS | Hydrogen 0-1000ppm only |
| SPXCDXSN1SS | Nitrogen Dioxide 0-50.0ppm (10.0-50.0ppm, 5.0ppm)** |
| SPXCDXSB1SS | Carbon Dioxide IR 0-2.00%Vol. only |

*For UL/c-UL versions simply change the letters in the part number for certification and entry e.g. first part number in table above would become SPXCDULNFX.

**For further details of user configurable ranges refer to "Detectable Gases and XCD Sensor Performance" table on page 6.

Note: Add 'M' to the end of the part number to order an XCD with the optional MODBUS output e.g. the first part number in the table would become SPXCDALMFXM.

Our Product Range



Fixed Gas Monitoring

Honeywell Analytics offers a wide range of fixed gas detection solutions for a diverse array of industries and applications including: Commercial properties, industrial applications, semiconductor manufacturers, energy plants and petrochemical sites.

- » Detection of flammable, oxygen and toxic gases (including exotics)
- » Innovative use of 4 core sensing technologies – paper tape, electrochemical cell, catalytic bead and infrared
- » Capability to detect down to Parts Per Billion (ppb) or Percent by Volume (%v/v)
- » Cost effective regulatory compliance solutions

Portable Gas Monitoring

When it comes to personal protection from gas hazards, Honeywell Analytics has a wide range of reliable solutions ideally suited for use in confined or enclosed spaces.

These include:

- » Detection of flammable, oxygen and toxic gases
- » Single gas personal monitors – worn by the individual
- » Multi-gas portable gas monitors – used for confined space entry and regulatory compliance
- » Multi-gas transportable monitors – used for temporary protection of area during site construction and maintenance activities

Technical Services

At Honeywell Analytics, we believe in the value of great service and customer care. Our key commitment is providing complete and total customer satisfaction. Here are just a few of the services we can offer:

- » Full technical support
- » Expert team on hand to answer questions and queries
- » Fully equipped workshops to ensure quick turnaround on repairs
- » Comprehensive service engineer network
- » Training on product use and maintenance
- » Mobile calibration service
- » Customised programmes of preventative/corrective maintenance
- » Extended warranties on products

Environmental and Gas Monitoring Ltd.
Unit 5 Barrmill Road
Galston
Ayrshire
KA4 8HH

Tel 01563 820444
Fax 01563 820163
www.egm-ltd.com
sales@egm-ltd.com

Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.